





## 9.3

## APPENDIX - DOOR &amp; EMBRASURE SCHEDULE

## DOOR &amp; EMBRASURE SCHEDULE – Rancho San Andrés Castro Adobe

1 of 3

#	Door		Hardware			Embrasure		Trim		Notes
	Type	Size	Hinge	Latch	Other	Size	Materials	Exterior	Interior	
						WxH @ door / WxH @ wall / Depth	Soffit / Left Reveal Right Reveal			
D1	A	Pair, Dutch 7'-6" x 7'3½" 7/8" thick	2 pair straps ea door section	Non op. brass thumb latch	dead bolt, slide bolt top, bot, cntr	NA	NA	none	none	Pair of Dutch doors, circ sawn 1"x7½" vertical planks w/ X & horiz bracing, carriage bolt décor. Door opening by Potter 1970s w/ old 6¾" square chamfered posts w/ Dutchmen at base
D2	B	Pair 3'-6" x 6'-0" 1¾" thick	2 pair 3½" 5 knuckle butts per door	slid bolts top bot, mort lock, dead bolt	slide bolts top, bot, cntr, door bell scar	2'-8¼" x 6'-2", 4'-9" x 6'-1", 1'-10½" deep	2 bds hnd plnd 15¾", 6¼", 13", 10½", 10¾", 12¼"	hand planed, mitered 1"x3" bead at wdo, profile at wall	hand planed, mitered 1"x3" bead at wdo, profile at wall	Pair of doors, 2 lites at top (1/1) w/ radius wood glass stops. Bottom 1 recessed framed panel molding int, ext. Worn old threshold. Doors are original
D3	C	3'-6" x 6'-2" 13/8" thick	2 pair 3½" 5 knuckle butts ball finials	lever thumb latch. Rim lock scar	slide bolt cntr. Filled key, knob holes. 70's knocker	3'-0" x 6'-4½", 3'-11" x 8'-0", 1'-11" deep	Soffit 3 bds circ sawn, rough, 3", 10½", 9½" Reveals adobe w/ mud plaster	1" x 4" rough, weathered	None	Pine door, 1 lite at top w/ metal frame, which opens sliding downward into pocket in door, with screen. Bottom 1 recessed panel. Brick sill w/ wood sill. Door & early American type thumb latch, Horclaw 1940's. Henson opening.
D4	D	3'-6"x 5'-10¾" 1¾" thick	3 pair 4" 5 knuckle butts	lever thumb latch	rim lock scar	2'-8" x 6'-0", 5'-2" x 6'-1½", 1'-10½" deep	2 bds hnd plnd 16½", 5 ¾", 9¾", 13¾", 9¾", 14"	hand planed, mitered 1"x3" bead at wdo, profile at wall	Hand planed, mitered 1"x3" bead at wdo, profile at wall	4 lites (2/2) at top with reset radius wood stops, 2 recessed framed panels w/ molding at bottom. Dutchman at top. May be modified 6 panel door. Fanned sill 3" high w/ heater inset Thumb latch early Am type, Horclaw 1940's.
D5	E D sim	2'-11½"x5'-10" 13/8" thick	3 pair 4" 5 knuckle butts per door	lever thumb latch	rim lock scar	4'-1" x 6'-1½", 4'-10½" x 6'-½", 10" deep	Soffit is lintel, 3 boards circ sawn, rough, 9" expd int x 2" Reveals adobe	None	None	4 lites (2/2) at top 11½"x 5¼" with square stops. 2 recessed panels at bottom, molding interior, plain exterior. Dutchman at top. Door set at center of wall, curved plastered reveals. Wood framed screen door on exterior. Sill high 1"
D6	F B sim	Pair 3'-6" x 6'-0" 1¾" thick	2 pr /door. 3½" 5 knkl butt N, 3" face mount, ball finial S	lever thumb latch, dead blot	none	2'-8" x 6'-2", 5'-0" x 6'-2¼", 1'-11" deep	2 bds hnd plnd 13½", 9¼", 13", 11¼", 12¼", 12"	hand planed, mitered 1"x3" bead at wdo, profile at wall	Hand planed, mitered 1"x3" bead at wdo, profile at wall	Pair of doors, 1 lite at top w/ square wood glass stops. Bottom 1 recessed framed panel molding int, ext. Worn old threshold. Doors are original but modified by Piazis. Molding similar to D2 but replaced.
D7	G	2'-1/2" x 6'- 2 1/2" 1" thick	3 straps	porcelain pull	none	NA	NA	NA	NA	2 vertical boards rough sawn ext, smooth int. 3 horizontal braces,
D8	H	2'-0" x 5'-9½" 1¾" thick	2 straps	wrought iron thumb latch	horizontal slide bolt	2'0"x 5'11"2'0" 2'0"x 5'11" 28¾" deep	4 bds 1¾" thick, 9½", 12½", 5", 8"	3 bds West 9¼", 12½", 5" East 8½", 11¼", 6 ¾"	Rough sawn 1"x3¾" head 1"x5¾" jamb	Single redwood plank; opening out of square (non-historic)
D9	J	2'-11½"x5'-11" 1¾" thick	3 pair 4" 5 knuckle butts ball finials	Non functional thumb latch	Bennington knob, slide bolt	3'-2" x 6'-2" 4'-6" x 6'-2" 2'-0" deep	2 bds hnd plnd Soffit 12½", 11" Reveal 10½", 14½"	Hand planed, mitered 1"x3" bead at wdo, profile at wall	Hand planed, mitered 1"x3" bead at wdo, profile at wall	Redwood door with 4 recessed panels, molding slightly different on nt & ext sim to D2. Wall adobe 28 ½" thick.

**DOOR & EMBRASURE SCHEDULE –Rancho San Andrés Castro Adobe**

**Continued**

#	Door		Hardware			Embrasure		Trim		Notes
	Type	Size	Hinge	Latch	Other	Size	Materials	Exterior	Interior	
						WxH @ door / WxH @ wall / Depth	Soffit / Left Reveal Right Reveal			
D10	K	2'-11"x5'-10½" 1¼" thick	2 pair 3½" 5 knuckle butts	Thumb latch	Scars of rimlck dr, keeper on E jamb	3'-1" x 6'-1" 4'-8½" x 6'-0" 2'-0" deep	2 bds hnd plnd Soffit 15" & 7¾" Reveal 11" & 13½"	Hand planed, mitered 1"x3" bead at wdo, profile at wall	Hand planed, mitered 1"x3" bead at wdo, profile at wall	4 recessed panels with simple narrow molding. three 4" hinge scars on west jamb,. Wall 28½" thick.
D11	M	2'-6" x 6'-8" 1¼" thick	2 pair 3½" 5 knuckle butts ball finials	Thumb latch	None	NA	NA	Plain ¾"x 3" butted	Plain ¾"x 3" butted	Louver door with frame at style and rail only, no cross framing.
D12	L	2'-0" x 6'-8" 1¼" thick	2 pair 3½" 5 knuckle butts, ball finials	Remington knob pull	None	NA	NA	Plain ¾"x 3" butted	none	Recessed single panel with molding.
D13	M	2'-6" x 6'-7½" 1¼" thick	2 pair 3½" 5 knuckle butts ball finials	Thumb latch	None	NA	NA	Plain ¾"x 3" butted	Plain ¾"x 3" butted	Louver door with frame at style and rail only, no cross framing.
D14	N	2'-6" x 6'-7" ¾" thick	2 pair 3½" 5 knuckle butts ball finials	Wood pull	None	NA	NA	Plain ¾"x 3" butted	Plain ¾"x1½" butted	Closet door of 3 smooth planed vertical continuous boards 9", 5½", 9", with horizontal braces eased edge ¾"x 6" on back near top and bottom.
D15	N	2'-6" x 6'-7" ¾" thick	2 pair 3½" 5 knuckle butts ball finials	Wood pull	None	NA	NA	Plain ¾"x 3" butted	Plain ¾"x1½" butted	Closet door of 3 smooth planed vertical continuous boards 9", 5½", 9", with horizontal braces eased edge ¾"x 6" on back near top and bottom.
D16	p R sim	2'-9" x 5'-11½" 1¼" thick	2 pair 4" 5 knuckle butts	Mortise lock, white porcelain knobs	Eastlake plate, horiz slide bolt	NA	NA	Hand planed, mitered 1"x3" bead at wdo, profile at wall	Hand planed, mitered 1"x3" bead at wdo, profile at wall	4 panels, beaded both sides, recessed with molding on exterior, flush with no molding on interior.
D17	Q	2'-5½" x 6'-1" ¾" thick	2 pair tiny 2½" 5 knuckle butts	Rim lock white porcelain knobs	None	NA	NA	hand planed, mitered 1"x3" bead at wdo, profile at wall	NA	Plank door of 3 smooth planed vertical boards 9½", 10" 9½". 1"x4" Z bracing on back.
D18	R P sim	2'-7¾"x 6'-1½" 1¼" thick	2 pair 3½" 5 knuckle butts	Mort. lock porce knob Eastlake detail	None	NA	NA	hand planed, mitered 1"x3" bead at wdo, profile at wall	hand planed, mitered 1"x3" bead at wdo, profile at wall	4 panels, beaded both sides, recessed with molding on exterior, flush with no molding on interior.
D19	S	2'-7½"x 6'-6" 1 3/8" thick	2 pairs 3½" pintle	Mortise lock, white porcelain knobs	None	NA	NA	hand planed, mitered 1"x3" bead at wdo, profile at wall	NA	4 recessed flat panels with molding. Recycled.

**DOOR & EMBRASURE SCHEDULE – Rancho San Andrés Castro Adobe**

**Continued**

#	Door		Hardware			Embrasure		Trim		Notes
	Type	Size	Hinge	Latch	Other	Size	Materials	Exterior	Interior	
						WxH @ door / WxH @ wall / Depth	Soffit / Left Reveal Right Reveal			
D20	S	2'-7½" x 6'-6" 1 3/8" thick	2 pairs 3½" pintle	Mortise lock, white porcelain knobs	None	NA	NA	hand planed, mitered 1"x3" bead at wdo, profile at wall	None	4 recessed flat panels with molding. Recycled.
D21	T	Pair 3'-8½" x 6'-1" 1 3/8" thick	2 pair 3½" 4 knuckle butts ball finials	No latch, metal knobs	Catch at top	NA	NA	hand planed, mitered 1"x3" bead at wdo, profile at wall	None	Pair with framed louvered top, framed recessed flat panel at bottom. Wood frame wall built out around book case to resemble embrasure.
D22	U	1"-12" x 5'-10" 1 1/8" thick	2 pair 3" 5 knuckle butts ball finials	Mortise lock with ornate brass knob & plate	None	NA	NA	hand planed, mitered 1"x3" bead at wdo, profile at wall	None	4 raised framed panels, no molding – s shaped edge.
D23	V W sim	2'-6" x 6'-1/2" 1½" thick	2 pair 3½" 5 knuckle butts ball finials	Mortise lock, white porcelain knobs	escutcheon missing on interior	NA	NA	hand planed, mitered 1"x3" bead at wdo, profile at wall	hand planed, mitered 1"x3" bead at wall, profile at wdo	4 panel door, raised framed panels with molding. Door cut down at top and bottom.
D24	W V sim	2'-0" x 6' ½" 1 1/8" thick	2 pair 3½" 3 knuckle butts ball finials	rimlock, white porcelain knobs	None	NA	NA	hand planed, mitered 1"x3" bead at wall, profile at wdo	hand planed, mitered 1"x3" bead at wall, profile at wdo	4 panel door, raised framed panels with molding.
D25	X	Pair of Bifolds 5'-0" x 6'-6½" ¾" thick	Pins at jamb, track at head	Small white porcelain pull	None	NA	NA	hand planed, mitered 1"x3" bead at wall, profile at wdo	hand planed, mitered 1"x3" bead at wall, profile at wdo	Thin bi-fold doors with louvers at top and framed flat panel at bottom.
D26	X	Pair of Bifolds 5'-0" x 6'-6½" ¾" thick	Pins at jamb, track at head	Mortise lock, white porcelain knobs	None	NA	NA	hand planed, mitered 1"x3" bead at wall, profile at wdo	hand planed, mitered 1"x3" bead at wall, profile at wdo	Thin bi-fold doors with louvers at top and framed flat panel at bottom.
D27	V W sim	2'-6" x 6'-1/2" 1½" thick	2 pair 3½" 5 knuckle butts ball finials	Mortise lock, white porcelain knobs	None	NA	NA	hand planed, mitered 1"x3" bead at wall, profile at wdo	hand planed, mitered 1"x3" bead at wdo, profile at wall	4 panel door, raised framed panels with molding

